



2026 YUSHUNXIN Fertilizer Equipment المعايير

حلول متكاملة لإنتاج الأسمدة، تسليم كامل.

Email: inquiry@fertilizerplantcost.com WhatsApp: +86 182 0399 3035

بيانات مرجعية لتخطيط عروض الأسعار. تؤكد المعايير والأسعار النهائية لكل مشروع.

عن هذا الكتيب

يجمع هذا الكتيب البيانات الفنية الرسمية حسب الموديل لشركة YUSHUNXIN المستخدمة في عروض الأسعار. جميع الموديلات بيانات مرجعية للتخطيط؛ تؤكد المعايير والأسعار النهائية لكل مشروع.

مكونات علامات تجارية اختيارية

الخيار	المكونات	تعديل السعر	ملاحظة
Option 1	W/N motors + Guomao gearboxes + ZWZ bearings	8-10%+	حزمة ترقية قيمة
Option 2	Siemens motors + SEW gearboxes + SKF bearings	12-15%+	علامات دولية ممتازة
ملاحظة	جهود وترددات أخرى ومواد خاصة قابلة للتخصيص	-	-

Disc Granulator (Pan Granulator)

Granulator

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXYP-2000	Disc granulator	kW 4	t/h 1.5–1.2	m 2.25×1.65×2.26	—	Pan Ø2000 mm · edge 450 mm · 14 r/min · reducer XWD5-71-4
SXYP-3000	Disc granulator	kW 11	t/h 4–2	m 3.1×2.2×3.4	—	Pan Ø3000 mm · edge 450 mm · 14 r/min · reducer ZQ350
SXYP-3600	Disc granulator	kW 18.5	t/h 6–4	m 3.8×2.9×4.1	—	Pan Ø3600 mm · edge 450 mm · 13 r/min · reducer ZQ400

Rotary Drum Granulator

Granulator

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXZGZ-1240	Rotary drum granulator	kW 5.5	t/h 2–1	Φ1200×4000 mm	—	r/min · shell 10 mm Q235B · inlet moisture 30% 17
SXZGZ-1560	Rotary drum granulator	kW 11	t/h 5–4	Φ1500×6000 mm	—	r/min · shell 12 mm Q235B 17.5
SXZGZ-1870	Rotary drum granulator	kW 15	t/h 8–5	Φ1800×7000 mm	—	r/min · shell 16 mm Q235B 11.5
SXZGZ-2080	Rotary drum granulator	kW 18.5	t/h 15–8	Φ2000×8000 mm	—	r/min · shell 16 mm Q235B 11
TDDG-2210	Rotary drum granulator	by model	t/h 15–8	Φ2200×10000 mm	—	For organic fertilizer granulation

New-Type Organic Fertilizer Granulator

Granulator

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXJC-600	New-type organic granulator	kW 37	t/h 1.5–1	mm 1150×1600×4100	t 1.85	Inlet moisture 30% · granule 3–6 mm · body 8 mm
SXJC-800	New-type organic granulator	kW 55	t/h 2.5–1.5	mm 1300×1850×4250	t 2.4	Inlet moisture 30% · granule 3–6 mm · body 8 mm
SXJC-1000	New-type organic granulator	kW 75	t/h 4–2	mm 1600×2350×4700	t 4	Inlet moisture 30% · granule 3–6 mm · body 10 mm
SXJC-1200	New-type organic granulator	kW 90	t/h 6–4	mm 1800×2550×4900	t 6.66	Inlet moisture 30% · granule 3–6 mm · body 10 mm

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXJC-1500	New-type organic granulator	kW 110	t/h 8–6	mm 2000×2800×5500	t 7.6	Inlet moisture 30% · granule 3–6 mm · body 10 mm

Double-Roller Extrusion Granulator

Granulator

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXDG-1T	Double-roller extrusion granulator	kW 11	t/h 1.5–0.8	mm 1350×750×1430	t 0.8	Roller sheet 151×220 mm · granule Ø3–10 mm · SS rollers
SXDG-1.5T	Double-roller extrusion granulator	kW 18.5	t/h 1.5≈	mm 1580×800×1560	t 0.96	Roller sheet 151×300 mm · granule Ø3–10 mm · SS rollers
SXDG-2T	Double-roller extrusion granulator	kW 22	t/h 2≈	mm 1580×800×1560	t 1.2	Roller sheet 186×300 mm · granule Ø3–10 mm · SS rollers

Flat-Die Pellet Mill

Granulator

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXPM-300	Flat-die pellet mill	kW 22	t/h 1–0.8	mm 1070×520×1270	—	Pellet Ø2–10 mm · feed 3–5 mm · moisture <20% · cylindrical pellets
SXPM-400	Flat-die pellet mill	kW 30	t/h 2–1	mm 1200×600×1350	—	Pellet Ø2–10 mm · feed 3–5 mm · moisture <20%
SXPM-600	Flat-die pellet mill	kW 55	t/h 4–2.5	mm 1200×1600×2000	—	Pellet Ø2–10 mm · feed 3–5 mm · moisture <20%

Compost Turner

Fermentation

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXXZ-2000	Moving type	hp 36	m³/h 500–400	mm 2000×2300×3000	—	Turning width 2000 mm · height 600–800 mm
SXLD-2400	Crawler	hp 75	m³/h 1000–800	mm 2700×2550×3500	—	Turning width 2400 mm · height 1100 mm
SXLD-2600	Crawler	hp 116	m³/h 1100–900	mm 3000×2750×3700	—	Turning width 2600 mm · height 1000–1300 mm
SXLD-3000	Crawler	hp 136	m³/h 1200–1000	mm 3000×2800×4200	—	Turning width 3000 mm · height 1300–1500 mm

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXLD-5000	Crawler (hydraulic)	kW / 336 hp 247	m³/h 1600	mm 4000×4200×6300	—	Turning width 5000 mm · height 2000 mm
SXGT-3000 / 4000 / 5000 / 6000	Groove	kW 49.25–16.85	by groove width	by model	—	Width 3–6 m · depth 0.8 m · ordinary / mechanical / hydraulic lifting
SXLPGD-10000	Wheel type	kW main 22	large-scale	—	t 10	Turning width 10 m · groove height 2 m · 24 turning teeth (Mn steel)

Chain Crusher

Crushing & Screening

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXLF-500	Chain	kW 11	t/h 3–1	mm 750×700×620	t 0.2	crushing chains · Q235B shell 8 mm 4
SXLF-600	Chain	kW 15	t/h 5–2	mm 800×750×820	t 0.52	crushing chains · Q235B shell 8 mm 4
SXLF-800	Chain	kW 22	t/h 8–5	mm 800×850×900	t 0.52	crushing chains · Q235B shell 8 mm 4

Vertical Crusher

Crushing & Screening

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXLS-600	Vertical (double feed silo)	kW 22	t/h 5–3	mm 1900×750×1300	t 0.66	double-edged blades · chains 8×2 12
SXLS-800	Vertical (double feed silo)	kW 30	t/h 8–5	mm 2100×1020×1800	t 0.83	double-edged blades · chains 8×2 12
SXLS-1000	Vertical (double feed silo)	kW 37	t/h 15–8	mm 2700×1220×2150	t 1.08	double-edged blades · rubber lining option 12

Horizontal Fertilizer Mixer

Mixing

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXWS-70	Horizontal batch mixer	kW 7.5	t/h 3–2	mm 1000×1200×2350	t 0.54	Reducer ZQ350-23.34
SXWS-90	Horizontal batch mixer	kW 11	t/h 5–3	mm 1000×1500×2550	t 0.61	Reducer ZQ350-23.34

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXWS-1015	Horizontal batch mixer	kW 15	t/h 7–5	mm 1930×1120×2410	t 1.02	Reducer ZQ500-23.34
SXDZ-8030	Single-shaft mixer	kW 7.5	t/h 3–2	mm 750×800×3700	—	Water spray system included
SXSZ-8030	Double-shaft mixer	kW 11	t/h 10–5	mm 750×800×3700	—	Reducer ZQ350-31.5 · water spray
SXSZ-1050	Double-shaft mixer	kW 22	t/h 20–15	mm 1200×1300×6200	—	Reducer ZQ500-31.5 · water spray

Rotary Fertilizer Dryer

Drying & Cooling

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXHG-15165	Rotary dryer	kW 11	t/h 6–4	mm 3060×17100×1500	—	Reducer ZQ350 · inlet ≥300 °C · angle 3–5° · 6 r/min · refractory-lined pipes included
SXHG-1518	Rotary dryer	kW 11	t/h 6–4	mm 3060×18600×1500	—	Reducer ZQ350 · inlet ≥300 °C · 6 r/min · Q235B 12 mm
SXHG-1616	Rotary dryer	kW 15	t/h 8–6	mm 3330×16300×1620	t 11.7	Reducer ZQ400 · 6 r/min · Q235B 12 mm
SXHG-1818	Rotary dryer	kW 22	t/h 8–5	mm 3400×3200×19600	t 17.2≈	Drum Φ1800×8000 mm · evap. up to 800 kg/h · thermal efficiency 72–80%
SXHG-2020	Rotary dryer	kW 37	t/h 15–8	mm 4500×4200×24000≈	t 26.8	Drum Φ2000×20000 mm · evap. 800–1500 kg/h · ZQ650 · VFD speed
SXHG-2222	Rotary dryer	kW 37	t/h 18–8	by model	t 31.7	Shell Φ2200×22000 mm · evap. 1.2–2.2 t/h · thermal efficiency 65–75%
SXHG-2424	Rotary dryer	kW 45	up to 30 t/h	by model	t 43.2	Shell Φ2400×24000 mm · inlet gas 600–850 °C · ZQ650 · gas burner 2.5–5.0 MW

Rotary Fertilizer Cooler

Drying & Cooling

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXHG-0808 (cooler)	Rotary cooler	kW 5.5	t/h 2–0.8	mm 1800×1400×8600	t 3.5≈	Drum Φ800×8000 mm · evap. max 180 kg/h · reducer ZQ250 · discharge moisture ≤8%
Cooling series	Rotary coolers	by model	matched to dryers	by model	—	Companion coolers for SXHG dryer series

Rotary Screening Machine

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXGS-1020	Rotary screen	kW 3	t/h 2–1	by model	—	r/min · reducer ZQ250 · anti-block hitting device 21
SXGS-1030	Rotary screen	kW 3	t/h 3–2	by model	—	r/min · reducer ZQ250 · anti-block hitting device 21
SXGS-1230	Rotary screen	kW 4	t/h 4–3	by model	—	r/min · reducer ZQ250 21
SXGS-1240	Rotary screen	kW 4	t/h 5–3	by model	—	r/min · reducer ZQ250 18
SXGS-1540	Rotary screen	kW 5.5	t/h 8–5	by model	—	r/min · reducer ZQ400 16
SXGS-1560	Rotary screen	kW 5.5	t/h 10–6	by model	—	r/min · reducer ZQ400 16
SXGS-1870	Rotary screen	kW 7.5	t/h 15–12	Φ1800×7000 mm	—	Aperture 2–50 mm · screen area ≈39.6 m ² · 15 r/min
SXSC-2080	Rotary screen	kW 11	t/h 20–15	by model	—	r/min · reducer ZQ400 11
SXZDS-1030	Vibrating screen	kW 0.55	t/h 3–2	mm (screen) 1000×3000	—	Q235B · two discharge ports

Fertilizer Coating Machine

Coating

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXCT-1200	Coated tank	kW 0.75+0.75	—	—	—	Mixing tank + control panel + pipe + nozzle + pump
TDCT-1040 / 1240 / 1250 / 1260 / 1270	Coating machine	by model	by model	by model	—	Body 10 mm boiler steel Q235B · coating tank + powder spray device
TDCT-1540 / 1560 / 1580 / 1860 / 1870	Coating machine	by model	by model	by model	—	Body 12 mm · reducer ZQ350 (on larger models) · rubber / SS lining +10%
SXPF-159-6 / 219-6 / 325-6	Powder coating machine	kW 4 / 2.2 / 0.75	by model	by model	—	Speed adjustable · 201SS or 304SS · serves coating machine

Automatic Fertilizer Batching System

Automation

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXBC-3	Automatic batching machine	by model	by model	by model	—	Silo 1.5 m ³ · error ±0.2% · PLC control panel · belt 550 mm × 0.5 m · silo qty customizable
Static / dynamic dosing	Dosing systems	by model	by model	by model	—	Static parallel or continuous dynamic dosing per line

QL Series Stainless Steel Urea Crusher

WSF Modules

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXUG-400	Double-roller urea grinder	kW 5.5+2.2	t/h 2–1	by model	—	stainless steel · grinding urea 304
QL-500	Stainless urea crusher	kW 5.5+3	t/h 2–1	by model	—	Reference feed <2.5 mm · output 20–30 mesh
QL-600	Stainless urea crusher	kW 7.5+4	t/h 3–2	by model	—	Reference feed <2.5 mm · output 20–30 mesh
QL-800	Stainless urea crusher	kW 11+5.5	t/h 6–4	by model	—	Reference feed <2.5 mm · output 20–30 mesh
QL-1000	Stainless urea crusher	kW 15+7.5	t/h 8–6	by model	—	Reference feed <2.5 mm · output 20–30 mesh

kg Automatic Fertilizer Packing Machine 50–25

Packaging

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXWP-001	Packing machine	by model	bags/min 6–4	by model	—	kg/bag · error ±0.2% · sewing machine + conveyor + control cabinet 50–20
SXWP-002	Hopper packing machine	by model	bags/min 8–6	by model	—	kg/bag · error ±0.2% 50–20
SXWP-003	Double-silo packing machine	by model	bags/min 13–6	by model	—	kg/bag · error ±0.2% 50–20
SXWP-004	Double-station packing machine	by model	bags/min 13–6	by model	—	kg/bag · error ±0.2% 50–20

Automatic Ton-Bag (FIBC) Packing Machine

Packaging

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
TDYH-1000	Granule / powder ton-bag packer	by model	granule 20 t/h · powder 15 t/h	m 3.2×1.8×4.2	—	kg/bag · accuracy ±0.5% · belt conveyor + air compressor included 2000–500

Robotic Fertilizer Palletizer

Packaging

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXMDR-120	Robot palletizer	kW robot + 0.5×4 kW conveyors 5	bags/h 600–500	mm 3790×7000×5000	—	kg bags · 1–12 layers · 360° arm · servo drive · air 0.6–1.0 MPa 50–20

High-Level Fertilizer Palletizer

Packaging

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXLZ-600	High-level palletizer	kW 11.25	bags/h 500–400	mm 3790×7000×5000	—	Stacking height 600–1600 mm · 6–8 layers · air 0.6–0.8 MPa

Semi-Wet Material Crusher

Crushing & Screening

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXBS-40	Semi-wet	kW 22	t/h 1.5–1	mm 1100×700×1200	t 0.47	Mn hammers ×50 pcs 16
SXBS-60	Semi-wet	kW 30	t/h 3–1.5	mm 1300×1450×1300	t 0.73	Mn hammers 16
SXBS-90	Semi-wet	kW 37	t/h 5–3	mm 1720×1660×1650	t 1.26	Mn hammers 16
SXBS-120	Semi-wet	kW 75	t/h 8–5	mm 2130×2600×2100	t 2.33	Mn hammers 16

Straw Crusher

Crushing & Screening

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXHM-420	Rice-husk hammer mill	kW 11	by model	by model	—	Screen adjustable · cyclone dust collector · straw, stems, wood chips
SXHM-600	Hammer crusher	kW 11	by model	by model	—	Screen adjustable · straw, stems, wood chips

BB Fertilizer Drum Mixer

Mixing

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXBJ-1240	Drum BB mixer	kW 5.5	by model	Φ1200×4000 mm	t 2.3	Angle 2–5° · speed 17 r/min · 10 mm shell
SXBJ-1560	Drum BB mixer	kW 11	by model	Φ1500×6000 mm	t 4.4	Angle 2–5° · speed 17.5 r/min · 12 mm shell
SXBJ-1870	Drum BB mixer	kW 15	by model	Φ1800×7000 mm	t 4.4	Angle 2–5° · speed 11.5 r/min · 12 mm shell
BB 5–10 t/h	BB revolving-drum mixer	kW 5.5+1.5	t/h 10–5	—	—	Drum Φ1.5 m · hopper 0.7 m³ · inclination 20° · 12.5 r/min

Static Parallel Dosing Machine

Automation

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXAF-2030 / 2040	Automatic feeding machine	kW 2.2+4+0.37	by model	silos 2×3 / 2×4 m	—	Silo 5 / 7 m³ · thickness 4 mm · VFD conveyor · inspection ladder + perforated strainer
SXPS-1212	Product silo	—	m³ 1.0	—	—	mm thickness · support included 4
SXBS-1220	Buffer silo	—	m³ 1.5	—	—	mm thickness · buffers material for packing 4
SZ-1.5	Screw scale	by model	t/h 10–0.01	—	—	Accuracy ≤0.5% · 304 stainless steel · for additives

Fertilizer Dust Collection System

Crushing & Screening

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXXC-900 / 1200 / 1500 / 1800	Cyclone dust collector	—	41000–3500 m ³ /h	Φ900–1800 mm	—	Efficiency 85–95% · ≤350 °C · rotary (star) valve discharge
SXXF-2000 / 2500	High-efficiency cyclone	—	70000–25000 m ³ /h	Φ2000 / 2500 mm · H 6.5 m	4 / 2.5 t	Efficiency 85–95% · ≤250 °C · pressure drop 800–1600 Pa
SXSM-900 / 1200 / 1500 / 2000 / 2200 / 2500	Water-curtain dust collector	kW 7.5 / 4 / 2.2 pump	26507–3435 m ³ /h	Φ900–2500 mm	—	Including support
SXMC-64	Pulse bag dust collector	kW ID fan 7.5	m ³ /h 6000–3000	m 3.6×2.1×1.8	—	bags Ø130 mm · ≥99.5% efficiency · emission ≤30 mg/Nm ³ · pulse- 64 jet cleaning
BCS-4	Batching dust collection	kW ID fan 11	11000–8000 m ³ /h	—	—	Silo dust covers + pipe + pulse bag collector

Fertilizer Conveying Equipment

Automation

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
B500 / B600	Belt conveyor	by model	by model	width 500 / 600 mm	—	V” rubber belt 4 layers 10 mm · support included”
BD-600	Big-angle belt conveyor	by model	by model	width 500 mm · length 10 m	—	Ribbed belt
B600-10	Mobile belt conveyor	kW 3+0.75	by model	by model	—	Moving wheels + angle adjusting device
E250 / SXNE50	Bucket elevator	kW 5.5	m ³ /h · lift ≤45 m 60–35	by model	—	Bucket 15.7 L · 300 mm pitch · double-row plate chain · ≤60 mm feed
SX159	Screw conveyor	kW 2.2	by model	length 4 m	—	Standard screw conveyor
MS-500	Iron separator	—	—	—	—	Permanent magnets · hanging type

Automatic Bucket Packing Scale

Packaging

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXBZ-02	Double-scale filling & weighing	kW 0.5	bags/min 30–20	mm 1800×840×710	kg 150	g–6 kg/bag · accuracy ≤±0.3% · 304 stainless steel 5

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXDC-2A	Liquid packaging machine	kW 0.1≥	bottles/h 480–240	mm 1436×850×1000	—	L · accuracy ≥0.1% · 304 stainless steel 50–1

Automatic Feeding Machine & Silos

Automation

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXAF-2030 / 2040	Automatic feeding machine	kW 2.2+4+0.37	by model	silos 2×3 / 2×4 m	—	Silo 5 / 7 m³ · 4 mm plate · VFD conveyor · inspection ladder + perforated strainer
SXPS-1212	Product silo	—	m³ 1.0	—	—	mm plate · support included · for packing storage 4
SXBS-1220	Buffer silo	—	m³ 1.5	—	—	mm plate · buffers material before packing 4
SZ-1.5	Screw scale	by model	t/h 10–0.01	—	—	Accuracy ≤0.5% · 304 stainless steel · for additives

Disc Feeder

Automation

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXPJ-1600	Disc feeder	kW 7.5	t/h 4–2	mm 1800×1600×1600	t 0.79	Disc Φ1.6 m · edge 400 mm
SXPJ-1800	Disc feeder	kW 7.5	t/h 5–3	mm 1800×1800×1800	t 0.84	Disc Φ1.8 m · edge 400 mm
SXPJ-2000	Disc feeder	kW 7.5	t/h 6–4	mm 1850×2000×2000	t 0.97	Disc Φ2.0 m · edge 400 mm
SXPJ-2200	Disc feeder	kW 7.5	t/h 8–6	mm 1850×2200×2200	t 1.05	Disc Φ2.2 m · edge 400 mm
SXPJ-2500	Disc feeder	kW 11	t/h 10–8	mm 2000×2500×2500	t 1.39	Disc Φ2.5 m · edge 400 mm
SXPJ-3000	Disc feeder	kW 15	t/h 12–10	mm 2000×3000×3000	t 1.6	Disc Φ3.0 m · edge 400 mm

Double-Stage Hammer Crusher

Crushing & Screening

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXPC-600×400	Double-stage hammer crusher	kW 15+18.5	t/h 15–10	mm 1630×926×2350	—	Inlet ≤100 mm · output ≤3 mm

MSW Shredder

Crushing & Screening

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
SXSH-600	MSW shredder	kW 2×7.5	t/h 1.5–1	mm 1700×900×1500	—	Feed 600×800 mm · output 2–3 cm · alloy blades

Raymond Mill System

Crushing & Screening

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
5R65	Raymond mill system	kW 7.5+7.5+1.1	t/h 2–1	by model	—	mm · mill + cyclone + bag filter 0.044–0.125
5R990	Raymond mill system	kW 75+55+7.5	t/h 6–5	by model	—	mm · ring Φ1280 mm · roll Φ410 mm 0.044–0.125
990	Raymond mill system	kW 30+22+3	t/h 5≈	by model	—	mm · mill + cyclone + bag filter 0.044–0.125
SX-4121	Raymond mill system	kW 75+75+7.5	t/h 10–8	by model	—	mm · ring Φ1280 mm · roll Φ210 mm 0.044–0.125

Hot Air Stove

Drying & Cooling

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
F-0.8 / 1.0 / 1.2	Hot air stove	—	small dryers	by model	—	Q235B shell · refractory interior
F-1.5	Hot air stove	—	medium dryers	by model	—	Q235B shell · refractory interior
F-1.8	Hot air stove	—	large dryers	—	—	Big size built on site with our drawings · gas / wood / coal

Induced Draft Fan

Drying & Cooling

الموديل	النوع	الطاقة	السعة	الأبعاد	الوزن	ملاحظات
4C	ID fan	kW 5.5	m³/h 5564–2932	—	—	Pressure 1501–2221 Pa · 3550 r/min
5C	ID fan	kW 7.5	m³/h 9870–5360	—	—	Pressure 1549–2265 Pa · 2900 r/min
6C	ID fan	kW 15	m³/h 20628–10314	—	—	Pressure 1733–2734 Pa · 2240 r/min
8C	ID fan	kW 22	m³/h 22435–17463	—	—	Pressure 1726–2501 Pa · 1600 r/min
10C	ID fan	kW 30	m³/h 43722–31237	—	—	Pressure 1505–1902 Pa · 1000 r/min
12C	ID fan	kW 55	m³/h 67457–63953	—	—	Pressure 1729–1859 Pa · 1000 r/min